

LIMBUS

CONTROL YOUR LIGHT



BY  *TD Lighting Solutions*



TLS64NI-W74L253-XX-IP Series

FAMILY DATASHEET



PRODUCT PICTURE



GENERAL SPECIFICATIONS

Product Code	TLS64NI-W74L253-30-IP
Description	HighBay Lighting
Degree (FWHM)	30°
Efficiency	92%
Type	64in1
Size (mm) W x L x H	253x74x9mm
Material / Operating Temp.	PMMA / -40°C ~ +80° C max / PC -35°C ~ +120°C
Fastening	Screw
Box Size (mm) WxLxH	320x245x105mm
Box Quantity	44 PCS
Box Weight (g)	
Rohs Compliant	
Storage Temperature	

PHOTOMETRIC SPECIFICATIONS



APPLICATION NOTES

- Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.
- Forbid to use industrial solvent to clean the lens, such as alcohol.
- Storage environment temperature is 0°C~40°C, humidity is 30%~95%.
- Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- Please wear gloves once install the lens, avoid to abrasion the lens surface.
- Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.



PRODUCT PICTURE



GENERAL SPECIFICATIONS

Product Code	TLS64NI-W74L253-60-IP
Description	HighBay Lighting
Degree (FWHM)	60°
Efficiency	92%
Type	64in1
Size (mm) W x L x H	253x74x8.8mm
Material / Operating Temp.	PMMA / -40°C ~ +80° C max / PC -35°C ~ +120°C
Fastening	Screw
Box Size (mm) WxLxH	320x245x105mm
Box Quantity	50 PCS
Box Weight (g)	
Rohs Complaint	
Storage Temperature	





PHOTOMETRIC SPECIFICATIONS




APPLICATION NOTES

- Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.
- Forbid to use industrial solvent to clean the lens, such as alcohol.
- Storage environment temperature is 0°C~40°C, humidity is 30%~95%.
- Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- Please wear gloves once install the lens, avoid to abrasion the lens surface.
- Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.

MECHANICAL DRAWINGS





PRODUCT PICTURE



GENERAL SPECIFICATIONS



Product Code	TLS64NI-W74L253-60-IP
Description	HighBay Lighting
Degree (FWHM)	90°
Efficiency	92%
Type	64in1
Size (mm) W x L x H	253x74x9mm
Material / Operating Temp.	PMMA / -40°C ~ +80° C max / PC -35°C ~ +120°C
Fastening	Screw
Box Size (mm) WxLxH	320x245x105mm
Box Quantity	50 PCS
Box Weight (g)	
Rohs Compliant	
Storage Temperature	

PHOTOMETRIC SPECIFICATIONS



APPLICATION NOTES

- Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.
- Forbid to use industrial solvent to clean the lens, such as alcohol.
- Storage environment temperature is 0°C~40°C, humidity is 30%~95%.
- Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- Please wear gloves once install the lens, avoid to abrasion the lens surface.
- Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.





PRODUCT PICTURE



GENERAL SPECIFICATIONS



Product Code	TLS64NI-W74L253-30x90-IP
Description	HighBay Lighting, Street Lighting
Degree (FWHM)	30x90°
Efficiency	92%
Type	64in1
Size (mm) W x L x H	253x74x9mm
Material / Operating Temp.	PMMA / -40°C ~ +80° C max / PC -35°C ~ +120°C
Fastening	Screw
Box Size (mm) WxLxH	320x245x105mm
Box Quantity	50 PCS
Box Weight (g)	
Rohs Complaint	
Storage Temperature	

PHOTOMETRIC SPECIFICATIONS



APPLICATION NOTES

- Please use a litter water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.
- Forbid to use industrial solvent to clean the lens, such as alcohol.
- Storage environment temperature is 0°C~40°C, humidity is 30%~95%.
- Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- Please ware gloves once install the lens, avoid to abrasion the lens surface.
- Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.



LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ

Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tlsteknoloji.com
+90 444 27 33